

Baxter



VIKING MOBILE LIFTS
M, L, AND XL





SAFE PATIENT HANDLING & MOBILITY REQUIRES A PATIENT-CENTERED APPROACH

Every day, care and support are tailored for each unique patient. What if equipment could do the same?

With the **Viking** lifts from **Baxter**, the right lift can be chosen for each scenario, supporting a consistent experience.

Available in a variety of sizes and lifting capacities, there is a **Viking** lift for your specific needs.

SUPPORT FOR EVERY PATIENT

VIKING M MOBILE LIFT

Compact and designed to meet
your most common lifting needs.

Safe working load: 205 kg / 450 lb



VIKING L MOBILE LIFT

Lift designed for your larger
patients.

Safe working load: 250 kg / 550 lb



Ease of use

- Intuitive user display includes lift count, battery usage and overload indicator.
- Optional **Quick-Release Hook System** makes it to change slingbars or add a scale.
- Hand control is designed to be easy to attach and access from the maneuvering handles.
- Two lift speeds support a variety of controlled lifting needs (**Viking L** and **XL** only).

Lightweight and mobile

- The lightweight design facilitates direct support for the patient, when and where it is needed.
- Optional armrests support patients while they walk.
- Large casters designed to help roll easily.

Designed for safety

- Safe working loads of up to 300 kg / 660 lb with **Viking XL** help you lift even your heaviest patients.
- Accessories like slings, slingbars and designed to help you adapt the lift for different needs - and can be used across all three models.

VIKING XL MOBILE LIFT

Able enough to support even the heaviest patients.

Safe working load: 300 kg / 660 lb



THE SUPPORT YOU NEED, WHEN AND WHERE YOU NEED IT

As patients move along the mobility continuum and through different care settings, their lifting needs change. The **Viking** line of mobile lifts help support them.



Lifting to and from a bed or chair



Treatment and repositioning



Lifting from the floor



Ambulation and gait training support

VIKING MOBILE LIFTS TECHNICAL SPECIFICATIONS

	VIKING M LIFT 2040045A	VIKING L LIFT 2040044	VIKING XL LIFT 2040043
Maximum Load	205 kg / 450 lb	250 kg / 550 lb	300 kg / 660 lb
Weight (ready to use)¹			
With lead battery	37.5 kg / 82.7 lb	39.7 kg / 87.5 lb	43.2 kg / 95.2 lb
With lithium ion battery	36.2 kg / 79.8 lb	38.4 kg / 84.7 lb	41.9 kg / 92.3 lb
Height	1390 - 2035 mm / 54.7" - 80.1"	1390 - 2030 mm / 54.7" - 80"	1500 - 2110 mm / 59.1" - 83.1"
Base			
Height	105 mm / 4.1"	140 mm / 5.5"	140 mm / 5.5"
Length	1275 mm / 50.2"	1360 mm / 53.5"	1420 mm / 55.9"
Width	680 - 1095 mm / 26.8" - 43.1"	695 - 1070 mm / 27.4" - 42.1"	815 - 1130 mm / 32.1" - 44.5"
Expansion	Electric	Electric	Electric
Casters			
Front	75 mm / 3" twin	100 mm / 4" twin 75mm / 3" twin	100 mm / 4" twin 75mm / 3" twin
Rear	75 mm / 3" twin	125 mm / 5" twin 100 mm / 4" twin	125 mm / 5" twin 100 mm / 4" twin
Control Box			
Audible low battery signal	When <25% power remains ^{2,3}	When <25% power remains ^{2,3}	When <25% power remains ^{2,3}
Service Information	Displayed	Displayed	Displayed
Lift counter	Displayed	Displayed	Displayed
Overload indicator	Displayed ³	Displayed ³	Displayed ³
Battery power indicator	Displayed ³	Displayed ³	Displayed ³
Lifting Speed [without load]	23 mm / 0.9" per sec	23 mm / 0.9" per sec and 17mm / 0.7" per sec	23 mm / 0.9" per sec and 17mm / 0.7" per sec
Maximum Lifting Height	1795 mm / 70.7"	1790 mm / 70.5"	1910 mm / 75.2"
Lifting Interval	1335 mm / 52.6"	1330 mm / 52.4"	1370 mm / 54"
Emergency Lowering	Electric and manual	Electric and manual"	Electric and manual
Sound Level	Sound Level 51 dbA	51 dbA	51 dbA
Battery	Lithium ion or Lead-acid gel	Lithium ion or Lead-acid gel	Lithium ion or Lead-acid gel
Hand Control	Wired	Wired	Wired
Protection Class	IPX4	IPX4	IPX4
Material	Aluminum	Aluminum	Aluminum
Slingbar Standard	Universal 450 Slingbar	Universal 450 Slingbar	Universal TwinBar 670
ACCESSORIES			
	LikoScale model 350, 200 ⁴ , 400 ⁴ Slingbar Cover Paddy Quick-Release Hook Armrest Lift Stretcher: OctoStretch	LikoScale model 350, 400 ⁴ Slingbar Cover Paddy Quick-Release Hook Armrest Lift Stretchers: FlexoStretch OctoStretch LikoStretch 600 IC	LikoScale model 350, 400 ⁴ Slingbar Cover Paddy Quick-Release Hook Armrest Lift Stretchers: FlexoStretch OctoStretch LikoStretch 600 IC

¹ Includes battery, SlingBar and charging cable.

² A buzzer will sound when pressing a push button on the hand control.

³ Also displayed on the hand control.

⁴ Available in the United States and Canada only.

FOR MORE INFORMATION, PLEASE CONTACT
YOUR BAXTER SALES REPRESENTATIVE.

For safe and proper use of the product mentioned herein, please refer to the appropriate Operator's Manual or Instructions for Use.

Baxter reserves the right to make changes without notice in design, specifications and models. The only warranty Baxter makes is the express written warranty extended on the sale or rental of its products.

bax.to/sphm

Baxter, FlexoStretch, LikoScale, LikoStretch, OctoStretch and Viking are trademarks of Baxter International Inc. or its subsidiaries.

US-CS123-250010 (v1.0) 05/2025